



Barcode Reader

Z-3060



With its elegant exterior and great flexibility, the Z-3060 is versatile in every sense. Have you dreamed of having omnidirectional or in-line scanning capabilities without compromising on size?

The answer is the Z-3060, a handheld scanner on an adjustable (swivel) base. Whether you're scanning small items or large items, at the counter or off the counter, and hands-free or hands-free, the Z-3060 meets all kinds of barcode scanning needs.

- *Supports omnidirectional (3D) and inline (2D) scanning*
- *Powerful scanning performance*
- *Z-SCAN+ (patented technology)*
- *Honored with the award: red dot design 2007*



Characteristics:

- **Light Source:** 650 nm visible laser diode (LVD)
- **Depth of Field:** 0 – 200 mm for UPC/EAN 100%
- **Scan Pattern:** 5 directions of scan field
- **Scan Rate:** Omnidirectional: 1,400 scans per second
- **Single-line:** 74 scans per second
- **Number of Scan Line:** 20
- **Minimum Bar Width;** 5 mil @ PCS 90%
- **Print Contrast:** 30% @ UPC/EAN 100%
- **Indicators (LED):** Three-color LED (blue, red & white)
- **Beeper Operation:** Programmable tone & volume
- **System Interfaces:** Keyboard wedge, RS-232, USB, wand emulation
- **Cable:** Standard 2m straight
- **Power Consumption:** 1.0 watts
- **Operating Current:** 200 mA typical
- **Laser Class:** CDRH Class IIa; IEC 60825 Class 2
- **EMC:** CE EN55022 B, FCC Part 15 Class B, VCCI, BSMI
- **Operating Temperature:** 0°C - 40°C (32°F - 104°F)
- **Storage Temperature:** -20°C - 60°C (-4°F - 104°F)
- **Humidity:** 5% - 95% RH (non-condensing)
- **Ambient Light Injection:** Up to 4,500 Lux (fluorescence)
- **Shock:** Designed to withstand 1.5 m drops
- **1D Barcodes:** UPC/EAN/JAN, UPC/EAN with supplementary, JAN 8 & JAN 13, ISBN/ISSN, Japanese Bookland EAN, Code 39, Code 39 with full, ASCII, trioptic Code 39, Codabar (NM7), Code 128, Code 128 with, full ASCII, Code 93, Interleaved 2 of 5 (ITF), Addendum 2 of 5, IATA Code, MSI/Plessy, China Postal Code, Code 32