



Fiscal Printer

FP700+



PC and sales software are required for use.

Printer working modes:

- *Recording*
- *Reporting*
- *Test*
- *Periodic reports*

Online communication with PC for programming, reading and reporting database of articles, sales, etc.

Fiscal Memory: 4,000 daily reports.

Interface and accessories:

- *Cash drawer exit,*
- *Display,*
- *RS - 232C,*
- *Ethernet,*
- *USB*



Printing Mechanism: Direct line thermal printer

Printing Width: 80 mm (640 dots)

Printing Resolution: 203 x 203 dpi (8 x 8 dpmm)

Printing Speed: Max 200 mm per second

Printable Font Sizes: Font A - 12 x 24 dots, Font B - 9 x 24 dots, Font C - 8 x 16 dots

Printable Barcode Types: 1D: EAN-13, EAN-8, Code 39, Code 128, Interleaved 2 of 5, Codabar

Paper Type: Thermal paper rolls

Paper Width: 82 and 58 mm

Paper Thickness: 60 to 150 µm

Roll Max Diameter: 102 mm

Paper Loading: Easy paper loading

Post Printing Features: Auto cutter

Operator Display: Graphic LCD, 4 lines x 22 characters (128x32), LED Back Light

Emulation: Datecs Proprietary Fiscal Protocol

Connectivity: RS 232C, USB 2.0 compatible, LAN – 100 Mbps (100BASE-TX), Cash Drawer through RJ11 connector, External Display through RJ11 connector, GPRS Module (Option), SAM Slot

LED Indication: Paper end, Cover open

Keyboard and Buttons: On/Off button, Feed button, 4 function buttons

Power Supply: AC 100 to 240 V, 50 to 60 Hz, DC 24 V, 2.1 A

Reliability:

150 km (Thermal head)

1.5 million cuts (Auto cutter)

Certificates: CE

Dimensions (W x D x H): 150 x 185 x 130 mm

Weight: 1700 g

Operational temperature range: -10 to 40 °C, 35 to 85 % RH

Storage temperature range: -20 to 60 °C, 10 to 90 % RH